












RVS - 316Ti - RVS - 1.4571 - RVS - 316Ti - RVS

PM Type	Slang (NW)	Persmantels		Bestel nr.	KG-230
		Afmetingen (mm)			Prijs
		D Uitw.	L		
PM 0 RVS <u>1 BREDE GROEF</u>  	5	14,0	27,0	PM 0 RVS NW 5	11,73
	6	16,0	32,0	PM 0 RVS NW 6	11,84
	8	19,0	32,0	PM 0 RVS NW 8	13,40
	10	21,0	31,0	PM 0 RVS NW10	14,52
	13	25,0	33,0	PM 0 RVS NW13	16,86
	16	29,0	36,0	PM 0 RVS NW16	22,22
	20	31,5	41,0	PM 0 RVS NW20	27,25
	25	40,0	50,0	PM 0 RVS NW25	40,09
T.b.v. R7/R8 en 1TS					
PM 1 RVS <u>1 GROEF</u>  	6	20,0	31,0	PM 1 RVS NW 6	14,07
	8	20,6	31,0	PM 1 RVS NW 8	14,74
	10	23,6	33,0	PM 1 RVS NW10	15,52
	13	27,0	35,0	PM 1 RVS NW13	16,86
	16	31,0	38,0	PM 1 RVS NW16	22,22
	20	35,0	44,0	PM 1 RVS NW20	27,25
	25	42,0	52,0	PM 1 RVS NW25	40,09
	T.b.v. 1SC				
PM 2 RVS <u>2 GROEVEN</u>  	6	21,0	31,0	PM 2 RVS NW 6	11,84
	8	22,5	31,0	PM 2 RVS NW 8	13,40
	10	26,5	33,0	PM 2 RVS NW10	14,52
	13	30,0	36,0	PM 2 RVS NW13	15,08
	16	34,0	38,0	PM 2 RVS NW16	20,10
	20	38,0	44,0	PM 2 RVS NW20	25,02
	25	47,0	52,0	PM 2 RVS NW25	37,97
	32	57,0	60,0	PM 2 RVS NW32	63,54
	40	65,0	73,0	PM 2 RVS NW40	81,52
	50	78,0	80,0	PM 2 RVS NW50	107,21
T.b.v. 2SK/2SN en 1SN					
PM 4 RVS <u>3 GROEVEN</u>  	6	22,0	34,0	PM 4 RVS NW 6	14,07
	10	26,0	38,0	PM 4 RVS NW10	15,52
	13	30,0	40,0	PM 4 RVS NW13	16,86
	16	33,0	40,0	PM 4 RVS NW16	22,22
	20	38,0	50,0	PM 4 RVS NW20	27,25
	25	45,5	60,0	PM 4 RVS NW25	40,09
	32	58,0	70,0	PM 4 RVS NW32	63,54
	40	65,0	73,0	PM 4 RVS NW40	81,52
	50	78,0	80,0	PM 4 RVS NW50	107,21
	T.b.v. 4SP				
PM 6 RVS <u>GEEN GROEVEN</u> 	6	15,0	30,0	PM 6 RVS NW 6	11,84
	8	17,0	30,0	PM 6 RVS NW 8	13,40
	10	18,0	30,0	PM 6 RVS NW10	14,52
	13	24,0	32,0	PM 6 RVS NW13	15,08
	16	28,0	30,0	PM 6 RVS NW16	20,10
	20	30,0	34,0	PM 6 RVS NW20	25,02
	25	36,0	45,0	PM 6 RVS NW25	37,97
	T.b.v. PTFE				

RVS - 316Ti - RVS - 1.4571 - RVS - 316Ti - RVS

PERSMAATTABEL

Persmantel	Slang / NW	5	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	---	----	----	----	----	----	----	----	----

PM 0 RVS




Niet schillen

R7	11,2	14,6	15,9	18,6	23	26	28,4	37	-	-	-
1TS	11,1	14,5	15,8	18,5	22	25	28	36,5	-	-	-
R8	11,1	14,3	15,7	18,3	23	26	29	37	-	-	-

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	----	----	----	----	----	----	----	----

PM 1 RVS



Niet schillen

1SC	16,2	17,3	20,5	24	28	31,8	38,5	-	-	-	
SL:	22	22	24	26	29	32	40	-	-	-	
SØ:	Tot op het staaldraad.										
2SK	PM:	17	17,4	20,6	24,5	28 ³	32,2	38,7	-	-	-

(3 = Persen met PM 3 -mantel!!)

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	----	----	----	----	----	----	----	----

PM 2 RVS




Niet schillen

1SN	16,5	17,7	21,4	24,8	28,7	32,3	40	48	56,6	70
2SN	17	18,7	22,5	25,7	29,6	33,5	42	50	58,6	71,7
2SK	16,4	17,7	21,4	24,8	28,7	32,3	40,4	-	-	-

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	----	----	----	----	----	----	----	----

PM 4 RVS



SL:	25	21	28	28	29	37	41	49	55	62
SØ:	Tot op het staaldraad.									

2ST	PM:	18,2	19	22	26	28,5	34,1	40,7	52,5	58,8	71,3
-----	-----	------	----	----	----	------	------	------	------	------	------

SL:	25	-	28	28	29	37	41	49	55	62
SD:	Tot op het staaldraad.									

4SP	PM:	19,4	-	22,6	25,9	29,2	34,9	41,5	54,3	61,4	*
-----	-----	------	---	------	------	------	------	------	------	------	---

Persmantel	Slang / NW	20	25	32	40	50
------------	------------	----	----	----	----	----

PM 4-S RVS



Schillengte uitw.	48,8	62,8	69,9	78,5	84,8
Schillengte inw.	15	17	21,5	22	29
Schildiam. inw./uitw.	Tot op het staaldraad.				

4SH	Persmaat	34	42	50,4	57,7	73,8
R15	Persmaat	34	42	-	-	-

Persmantel	Slang / NW	32	40	50
------------	------------	----	----	----

PM 6-S RVS



Schillengte uitw.	74	81	85
Schillengte inw.	21,5	22	29
Schildiam. inw./uitw.	Tot op het staaldraad.		

R15/R13	Persmaat	56,1	63	77,6
---------	----------	------	----	------

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	----	----	----	----	----	----	----	----

PM 5 RVS

3TE	16,1 ²	18,8	20,4	24,2	29	32,2	39,5	45,2	*	*
-----	-------------------	------	------	------	----	------	------	------	---	---

(2 = Persen met PM 2 -mantel!!)

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
------------	------------	---	---	----	----	----	----	----	----	----	----

PM 6 RVS



Niet schillen

PTFE	13	13,8	15,5	20,5	23,5	27	34	-	-	-
------	----	------	------	------	------	----	----	---	---	---

(Alle maten zijn gegeven in MM. De persdiameter kan zich i.v.m. toleranties enigszins wijzigen.)

Stand: Januari 2008