











PM Type	Slang (NW)	Persmantels		Bestel nr.	KG-220
		Afmetingen (mm)			Prijs
		D	L		
PM 0 <u>1 KARTEL RAND</u> 	4	13,0	24,0	PM 0 NW 4	1,48
	5	15,0	26,0	PM 0 NW 5	0,93
	6	17,0	29,0	PM 0 NW 6	0,76
	8	20,0	30,5	PM 0 NW 8	1,19
	10	22,0	32,0	PM 0 NW10	1,28
	13	27,0	32,5	PM 0 NW13	1,81
	16	31,0	37,0	PM 0 NW16	2,83
	20	34,5	41,0	PM 0 NW20	3,75
	25	40,0	50,0	PM 0 NW25	6,63
	T.b.v. R7/R8 en 1TS				
PM 1 <u>1 GROEF</u> 	6	19,0	23,0	PM 1 NW 6	0,87
	8	20,0	27,5	PM 1 NW 8	1,12
	10	23,0	30,0	PM 1 NW10	1,28
	13	26,5	32,0	PM 1 NW13	1,69
	16	29,0	35,0	PM 1 NW16	3,06
	20	33,0	34,0	PM 1 NW20	3,58
	25	42,0	45,0	PM 1 NW25	7,46
	32	54,0	50,0	PM 1 NW32	10,85
	40	62,0	55,0	PM 1 NW40	20,99
	50	76,0	60,0	PM 1 NW50	27,09
T.b.v. 1SC en 1SN					
PM 2 <u>2 GROEVEN (NW25=1 GROEF)</u> 	6	22,0	26,0	PM 2 NW 6	1,10
	8	24,0	27,5	PM 2 NW 8	1,36
	10	26,0	30,0	PM 2 NW10	1,48
	13	30,0	32,5	PM 2 NW13	1,99
	16	34,0	35,0	PM 2 NW16	2,71
	20	38,0	40,0	PM 2 NW20	3,52
	25	45,0	50,0	PM 2 NW25	6,29
	32	60,0	57,0	PM 2 NW32	13,63
	40	67,0	62,0	PM 2 NW40	20,69
	50	80,0	66,0	PM 2 NW50	32,44
T.b.v. 3TE / 2SK en 2SN					
PM 3 <u>3 GROEVEN</u> 	8	21,0	29,0	PM 3 NW 8	1,17
	10	23,0	31,5	PM 3 NW10	1,35
	13	27,0	34,0	PM 3 NW13	1,94
T.b.v. 2SW					
PM 4 <u>4 GROEVEN</u> 	6	22,0	30,0	PM 4 NW 6	1,77
	10	26,0	32,5	PM 4 NW10	1,73
	13	30,0	35,0	PM 4 NW13	2,36
	16	34,0	38,5	PM 4 NW16	3,09
T.b.v. 4SP					

PER SMAATTABEL


Persmantel	Slang / NW	5	6	8	10	13	16	20	25	32	40	50	
PM 0 		Niet schillen											
	R7	11,6	14,4	16,2	18,3	22,8	26,3	28,4	37	(NW4=11mm)			
	1TS	11,8	14,1	15,9	18,1	22,1	-	28	36,5	-	-	-	
	R8	11,8	13,8	15,8	18	22,8	25	29	36,1	-	-	-	


Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50	
PM 1 		Niet schillen										
	1SC	PM:	15	16,3	18,7	22,2	25,3	29	37	-	-	-
	1SN	PM:	-	-	-	-	-	-	-	47	53,9	68,3
	R4							21 ²	21 ²	?	56,1	?
	3TE									47,9	55	


(2 = Persen met PM 2 -mantel!!)


Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50	
PM 2 		Niet schillen										
	1SN	PM:	16,4	18,3	19,8	23,2	27,3	30,8	38,5	-	-	-
	2SK	PM:	16,5	18,5	20,2	24	27,8	31,9	39	-	-	-
	2SN	PM:	17,2	19,2	21,2	24,3	28,2	32,3	41 ¹²	52	58,4	72,3
	3TE	PM:	18,2	21,5	22,5	26,9	31,0	34,9	41,2			


(12= Persen met PM12 mantel)

Persmantel	Slang / NW	6	10	13	16	20	25	32	40	50	
PM 3 	SL:	-	20	23	27	-	-	-	-	-	
	SØ:	Tot op het staaldraad.									
	2SW	PM:	-	17,9	20	23,7	-	-	-	-	-

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50
PM 4 	SL:	18	-	22	24	27	-	-	-	-	-
	SØ:	Tot op het staaldraad.									
	4SP	PM:	19	-	23	26,5	30,5	-	-	-	-

Persmantel	Slang / NW	20	25	32	40	50	
PM 4-NS 		Niet schillen					
	4SP	Persmaat	35,9	42,5	-	-	-
	4SH	Persmaat	35,9	42,1	50,6	60	68,8
	R15	Persmaat	35,8	42,1	-	-	-

Persmantel	Slang / NW	20	25	32	40	50
PM 6-NS 		Schillengte uitw.				
		-	-	53	69	78
		Schildiam. uitw.				
		Tot op het staaldraad.				
	R15	Persmaat	-	-	51,3	60,8
R13	Persmaat	-	-	-	-	75,7

Persmantel	Slang / NW	6	8	10	13	16	20	25	32	40	50	
PM 6 / 7 		Niet schillen										
	PTFE	PM 6:	13	13,8	15,5	20,5	23,5	27	34	-	-	-
	PTFE/G	PM 7:	12,2	-	16,8	20,2	24	26,3	34	41	48,2	60,2

(Alle maten zijn gegeven in MM. De persdiameter kan zich i.v.m. toleranties enigszins wijzigen.)

Stand: April 2011

Persmaten met ? Volgen zsm !!